	GROT		1	J → J	*	i
		М	PC	MM	HP	KG
7010	Grot 2,2/5	2,20	5	500	180	2250
7000	Grot 3,0/5	3,00	5	675	180	2580
7005	Grot 3,0/7	3,00	7	450	260	2900

	GROT-NS	\leftarrow		J → J	*	i
		М	PC	ММ	HP	KG
7050	Grot 2,2/5 NS*	2,20	5	500	180	2560
7055	Grot 3,0/5 NS*	3,00	5	675	180	2877
7060	Grot 3,0/7 NS*	3,00	7	450	260	3175

^{*} hydropneumatic non stop protection system

OPTIONAL EQUIPLENT

- Reversible weld-on share point (pc)
- Side spike roller d=560 mm (left & right)
- LED lights



Chisel plow GROT











Chisel plow GROT

GROT is available in two working widths with a choice of shear bolt or nonstop protection (NS type) versions. GROT chisel plows are a great alternative to a traditional plow. They make it quick and cheap work replacing the traditional plow. Chisel plows can work at great depths (approx. 55 cm), even in extremely difficult soil conditions. When chisel plows work at a great depth, hard soil layers are torn off, the soil is loosened, and crop residues are covered. Working system consists of adjustable side wing shares, replaceable shin blades and reversible sharepoints. Double spike roller section provides better field compression and aeration. Hydraulic working depth adjustment is a standard GROT equipment. There are few paid options available such as: folding side rollers (recommended for 7-teeth versions), reinforced sharepoints, traffic LED lights.



Mandam Sp. z o.o. Poland 44-100 Gliwice, ul. Toruńska 14 0048 32 232 26 60 mandam.com.pl







